PRODUCT INFORMATION

Cheermo QH-ZR908-2 Description

Product Name	PI25/CL62/TLT75
Description	25μ polyimide/acrylic/75μ transparent PET
Specification	Width 1020mm*Length 500M / Roll

Feature

*Tested to uphold UL94 VTM-0 flame retardant standards.
*Facestock made of high temperature resistant polyimide material, which can withstand 285℃ without discoloration,embrittlement or deformation.
*Pressure Sensitive Adhesive(PSA) with high adhesion, no warping or rebound.
*Excellent insulation and voltage withstanding performance, good puncture resistance.

Main Application

*Lithium battery edge wrapping, PCBA labeling, FPC soft cable reinforcement.
*Polymer battery edge wrapping, positive and negative of the battery edge shielding.

Technical Data

Face material	Polyimide	Release liner	PET
Thickness of facestock	25±2 μ	Colour of liner	Transparent
Type of adhesive	Acrylic, Permanent	Thickness of liner	75±3 μ
Grinding steel adhesion	1.2~1.8 kgf/in	Release force	5~15 g/in
Tack	2.3±0.4 kgf/in	Service temperature	-20~200℃
Shearing force	≥72		

Approvals and certifications

This product complies with the certifications of UL standards. For further compliance information, please consult our specialist staff for the individual Declaration of Conformance (DoC) document of each product component.

Disclaimer

All technical information and data above mentioned shall be considered as average values and are not appropriate for a standard. Users are responsible for determining whether the product is fit for a particular purpose and suitable for the users' method of application. This publication does not constitute any warranty, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.Cheermo cannot assume any liability for the use of our products in conjunction with other materials. If you have any doubt, please feel free to contact us for technical support.