

## Polyester Webbing Slings

## YXS型圆形吊装带

### Round Webbing Slings

圆形吊装带都是圆形而无环眼状。圆形吊装带外层为特质的双层耐磨套管对接成环型，外套管不承重，只对平行排列的丝束起保护作用。在严重超载或长期使用而造成承载线芯有局部损伤时，其外套会首先断裂警示可避免事故的发生。如果圆形吊装带套管上有大的割伤必须经过检查，以判断是否可以修复或继续使用。在任何情况下，如果使用者不能确定被损害的程度，最好将圆形吊装带送回厂家来做进一步的检查。

适用范围：

特别适合圆环物体的吊装。

YXS圆形吊装带特点：

- 1、吊装带外表精细柔软，对易损伤的物体不会造成损坏。
- 2、吊装方式多，可用于拖拉被吊物体。
- 3、吊装带受力均匀，从而延长吊装带使用寿命。
- 4、可增加抗磨及防切断保护套。
- 5、设有独特标签，并使用国际标准色来区分承载吨位，即使吊装带磨损也易于辨认。

Round sling has the maximum load up to 3000T, effective length up to 100m, safety factor adopted is normally 7:1, 6:1.

Round sling is made of high tension industrial yarn (100%PES), the strands inside are as a form of endless cycle. The outside sleeve is also made of 100%PES, not for the Loading, but to protect the strands inside.

Round slings are the ideal solution for the safe lifting of loads, whether this is to be at your works, for loading and unloading or for use at a building site. The round slings will protect items being lifted, if the sling is damaged badly, the outside sleeve is breakage, and the outside strands will go out, so the sling can not use any more. Their sturdy core and a covering layer will guarantee a long serviceable life, even when in continuous use, round slings are also repairable.

Model: YXS



### YXS型圆形吊装带参数：

#### SPFCIFICATION

#### YXS Round Sling's lifting method and maximum Safety Working Load parameter.

型号 Model	载荷 Capacity (Ton)	宽度 WIDTH (mm)	一根吊带承重限度 Working load limit with 1 webbing sling							两根吊带承重限度 Working load limit with 2 webbing sling			
			垂直吊升 Straight	栓结吊升 Choked	不同角度的吊升 Lift in different angle					垂直吊升 Straight	栓结吊升 Choked	垂直吊升 Straight	栓结吊升 Choked
					0°-7°	7°	7°-45°	45°-60°	45°-60°				
					100%	80%	200%	140%	100%				
YXS-10	1	25/30	1000	800	2000	1400	1000	700	500	1400	1120	1000	800
YXS-20	2	50/60	2000	1600	4000	2800	2000	1400	1000	2800	2240	2000	1600
YXS-30	3	75/90	3000	2400	6000	4200	3000	2100	1500	4200	3360	3000	2400
YXS-40	4	100/120	4000	3200	8000	5600	4000	2800	2000	5600	4480	4000	3200
YXS-50	5	125/140	5000	4000	10000	7000	5000	3500	2500	7000	5600	5000	4000
YXS-60	6	150	6000	4800	12000	8400	6000	4200	3000	8400	6720	6000	4800
YXS-80	8	200	8000	6400	16000	11200	8000	5600	4000	11200	8960	8000	6400
YXS-100	10	250	10000	8000	20000	14000	10000	7000	5000	14000	11200	10000	8000
YXS-120	12	300	12000	9600	24000	16800	12000	8400	6000	16800	13440	12000	9600

## Polyester Webbing Slings

## YXS-B型圆形吊装带

### Round Sling Single Or Double Ply With

Model: YXS-B

圆形吊索最大载荷可达3000T, 有效长度可达100m, 采用的安全系数通常为7:1,6:1。圆形吊索由高张力工业丝(100%PES)制成, 内部的股线是无限循环的一种形式。外套也是由100%PES制成, 不是用于装载, 而是用于保护内部的股线。

圆形吊索是安全吊装货物的理想解决方案, 无论是在您的工作, 装卸货物还是在建筑工地使用。圆形吊索可以保护被吊起的物品, 如果吊索损坏严重, 外套破损, 外侧绳索将会外漏, 因此吊索不能再使用了。坚固的内芯和覆盖层将保证长使用寿命, 即使在连续使用时, 圆形吊索也可以修复。



Round sling has the maximum load up to 3000T, effective length up to 100m, safety factor adopted is normally 7:1, 6:1.

Round sling is made of high tension industrial yarn (100%PES), the strands inside are as a form of endless cycle. The outside sleeve is also made of 100%PES, not for the Loading, but to protect the strands inside. Round slings are the ideal solution for the safe lifting of loads, whether this is to be at your works, for loading and unloading or for use at a building site. The round slings will protect items being lifted, if the sling is damaged badly, the outside sleeve is breakage, and the outside strands will go out, so the sling can not use any more. Their sturdy core and a covering layer will guarantee a long serviceable life, even when in continuous use, round slings are also repairable.

### YXS-B型圆形吊装带参数:

#### SPFCIFICATION

#### YXS-B Round Sling's lifting method and maximum Safety Working Load parameter.

型号 Model	载荷 Capacity (Ton)	宽度 WIDTH (mm)	颜色 Color	一根吊带承重限度 Working load limit with 1 webbing sling						两根吊带承重限度 Working load limit with 2 webbing sling				最小长度 (m) Min.L (m)	最大长度 (m) Max.L (m)				
				垂直吊升 Straight	栓结吊升 Choked	不同角度的吊升 Lift in different angle				垂直吊升 Straight	栓结吊升 Choked	垂直吊升 Straight	栓结吊升 Choked						
						0°-7°	7°	7°-45°	45°-60°							45°	45°	45°-60°	45°-60°
						100%	80%	200%	140%							100%	70%	140%	112%
YXS-10B	1	50		1000	800	2000	1400	1000	700	1400	1120	1000	800	1	100				
YXS-20B	2	60		2000	1600	4000	2800	2000	1400	2800	2240	2000	1600	1	100				
YXS-30B	3	70		3000	2400	6000	4200	3000	2100	4200	3360	3000	2400	1	100				
YXS-40B	4	75		4000	3200	8000	5600	4000	2800	5600	4480	4000	3200	1	100				
YXS-50B	5	80		5000	4000	10000	7000	5000	3500	7000	5600	5000	4000	1	100				
YXS-60B	6	90		6000	4800	12000	8400	6000	4200	8400	6720	6000	4800	1	100				
YXS-80B	8	100		8000	6400	16000	11200	8000	5600	11200	8960	8000	6400	1	100				
YXS-100B	10	110		10000	8000	20000	14000	10000	7000	14000	11200	10000	8000	1	100				
YXS-120B	12	125		12000	9600	24000	16800	12000	8400	16800	13440	12000	9600	1	100				
YXS-150B	15	150		15000	12000	30000	21000	15000	10500	21000	16800	15000	12000	1	100				
YXS-200B	20	180		20000	16000	40000	28000	20000	14000	28000	22400	20000	16000	1	100				
YXS-250B	25	200		25000	20000	50000	35000	25000	17500	35000	28000	25000	20000	1	100				
YXS-300B	30	220		30000	24000	60000	42000	30000	21000	42000	33600	30000	24000	1	100				
YXS-400B	40	250		40000	32000	80000	56000	40000	28000	56000	44800	40000	32000	1	100				
YXS-500B	50	270		50000	40000	100000	70000	50000	35000	70000	56000	50000	40000	1	100				
YXS-600B	60	280		60000	48000	120000	84000	60000	42000	84000	67200	60000	48000	1	100				
YXS-800B	80	300		80000	64000	160000	112000	80000	56000	112000	89600	80000	64000	1	100				
YXS-1000B	100	320		100000	80000	200000	140000	100000	70000	140000	112000	100000	80000	1	100				

## Polyester Webbing Slings

### Product

**Polyester 1-Ply webbing belt for slings, 100% high tensile polyester(PES).**

### Technical Specifications

1. Colour coded according to DIN-EN1492-1.
2. Capacity stripes: each stripe is equal to 1 tonne capacity.
3. Each 25 to 300mm belt width is equal to all capacity, depending on order's request.
4. 200M per roll or any length as per order's request.
5. All the safety factor 5:1, 6:1, 7:1 is on the basis of double ply webbing sling, which is made of two 1-ply belt.

#### Characteristics

\*Low elongation.

#### Norms

\*According to EC Directive 98/37/EC.



型号 Name	织带宽度 Belt Width (mm)	Color regard to DIN-EN 1492-1	2层织带吊索的工作载荷 Working load limit of 2-ply webbing sling (t)	每200米的净重 N.W of 200m (kgs)			纸箱尺寸 Dimension of Carton (mm)
				5:1	6:1	7:1	
LBWB25	25		1	14	17	19	55*40*27
LBWB30	30		1	14	17	19	
LBWB50	50		2	27	34	38	
LBWB60	60		2	27	34	38	
LBWB75	75		3	42	50	57	
LBWB90	90		3	42	50	57	
LBWB100	100		4	55	66	76	
LBWB120	120		4	55	66	76	
LBWB125	125		5	69	83	95	
LBWB140	140		5	69	83	95	
LBWB150	150		6	82	98	114	
LBWB200	200		8	124	130	160	
LBWB250	250		10	156	164	208	
LBWB300	300		12	186	202	220	