

# Turnbuckles

# 美式模锻花兰螺丝

## Turnbuckles U.S. Federal Specification (FF-T-791B, TYPE1, FORM1)

用途：用于连接、紧固、吊装、起重的索具配件。

材质：合金钢、碳钢、不锈钢。

特点：具有刚强度、高韧性、耐磨、耐腐蚀、耐低温、耐高温等。

Drop forged, Quenched & Tempered.

Hot dipped galvanized.

Size from 1/4" to 2-3/4"

Different type available : E/E, H/H, E/H, J/E, J/J, etc.

美式模锻花兰螺丝参数：

### SPFCIFICATION



规格 Size(in.)	螺纹闭合时 总平均长度 Average Overall Length with Ends in Closed Position	每个重量(近似) Approx.Weight Each(lbs)					极限工作载荷 Working Load Limit(lbs)		
		眼&眼/钩&钩 Eyes and/or Hooks	叉&眼 Jaw & Eyes	叉&叉 Jaw & Jaw	连杆端 Stub End	花兰螺丝主体 Bodies Only	双钩/钩&眼 Hood & Hook Hood & Eye	双眼/叉&眼/叉 &叉/连杆端 Eye & Eye; Jaw & Eye Jaw & Jaw; Stub End	
1/4x4	8-1/4	0.30	0.30	0.40	0.29	0.17	0.400	500	
5/16x4-1/2	9-9/16	0.50	0.35	0.58	0.46	0.25	0.700	800	
3/8x6	11-7/8	0.75	0.82	0.93	0.75	0.30	1.000	1.200	
1/2x6	13-5/16	1.50	1.62	1.68	1.36	0.55	1.500	2.200	
1/2x9	16-5/16	1.75	1.82	1.85	1.69	0.74	1.500	2.200	
1/2x12	19-5/16	2.18	2.19	2.20	2.0	0.93	1.500	2.200	
5/8x6	15-1/2	2.63	2.59	2.82	2.15	0.91	2.250	3.500	
5/8x9	18-1/2	3.00	3.01	3.25	2.70	1.20	2.250	3.500	
5/8x12	21-1/2	3.25	3.50	3.75	3.22	1.50	2.250	3.500	
3/4x6	17	3.75	4.25	4.688	3.25	1.30	3.000	5.200	
3/4x9	20	4.50	5.00	5.38	4.00	1.70	3.000	5.200	
3/4x12	23	5.75	5.75	6.12	4.65	2.12	3.000	5.200	
3/4x18	29	7.00	7.25	7.25	6.12	2.93	3.000	5.200	
7/8x6	18	-	-	-	4.75	2.00	4.000	7.200	
7/8x12	24-5/8	8.38	8.88	9.36	6.62	3.00	4.000	7.200	
7/8x18	30-5/8	10.25	10.60	11.44	8.75	4.12	4.000	7.200	
1x6	20-5/8	-	-	-	6.41	2.50	5.000	10.000	
1x12	26-5/8	11.25	12.00	12.88	8.90	3.86	5.000	10.000	
1x18	32-5/8	14.00	14.75	16.10	11.70	5.50	5.000	10.000	
1x24	38-5/8	17.00	17.75	18.60	14.30	7.00	5.000	10.000	
1-1/4x6	20	-	-	-	10.40	4.00	6.500	15.200	
1-1/4x12	29-7/8	19.00	21.20	23.60	14.20	5.93	6.500	15.200	
1-1/4x18	35-7/8	24.10	26.00	26.60	18.00	8.00	6.500	15.200	
1-1/4x24	41-7/8	25.10	28.70	31.20	21.80	10.00	6.500	15.200	
1-1/2x6	22-7/8	-	-	-	15.40	5.80	7.500	21.400	
1-1/2x12	32-3/8	27.00	31.10	35.50	20.50	8.40	7.500	21.400	
1-1/2x18	38-3/8	31.20	36.40	40.70	26.20	11.50	7.500	21.400	
1-1/2x24	44-3/8	38.20	44.20	47.60	31.40	14.10	7.500	21.400	
1-3/4x6	-	-	-	-	22.70	8.75	-	28.000	
1-3/4x18	41-3/4	45.00	48.80	52.40	-	-	-	28.000	
1-3/4x24	47-3/4	58.00	60.00	64.00	43.90	19.50	-	37.000	
2x6	-	-	-	-	31.50	12.50	-	37.000	
2x24	51-3/4	90.00	102.00	115.00	60.30	27.50	-	60.000	
2-1/2x6	-	-	-	-	60.80	27.00	-	60.000	
2-1/2x24	51-1/2	183.00	180.00	200.00	110.00	54.00	-	60.000	
2-3/4x24	61-1/2	180.00	214.00	248.00	-	54.00	-	75.000	