



Professional LED Light Manufacturer  
For over 17 years

## FEATURES & BENEFITS


- RGBW Color Changing / Chasing / Fading
- High Brightness Output
- The Neon Flex Can Be Recessed Or Surface Mounted
- Installation Indoor Or Outdoor Available

- High Quality, Rest Assured Service

- salt Water Resistant
- Solvent Resistant
- Uv Resistant
- Flame Resistant

## HORIZONTAL BEND 16X16MM LED NEON FLEX, RGBW, 24V

SKU: WJ-SNF-1616-RGBW-24V




## TECHNICAL INFORMATION

### ■ Neon Specifications

SKU Code	WJ-SNF-1616-RGBW-24V
Voltage	24V
Watts/M	16W/M
Colour	RGBW Colors Changing
Lumens/M	300 LM
Guarantee	3 Years
Min Bend Diameter	120mm
CRI	90
Dimension	16mm x 16mm
IP Rating	IP65 IP68
IK Rating	IK08
Cut Points	Every 8.33cm(24v)
Operating Temp	-20°C to +45°C
Lifespan	Up to 36000 Hours
Certification	CE, RoHs, Reach
Material	Food Grade Silicone
LED Type & Quantity	SMD5050 72LEDs/M ( 4 IN 1 )

### ■ Driver Require

1 Meter	> 20W
2 Meters	> 40W
3 Meters	> 60W
4 Meters	> 80W
5 Meters	> 100W




■ DESCRIPTION

LED Neon Flex is an innovative lighting system made in energy-saving LED technology. Its flexible, soft construction and uniform light color makes Neon Flex a perfect alternative to traditional neon tubes.

Wilgex LED Neon flex could be widely used as signage lighting in shop , as decorative lighting at home, in office and restaurant and as a building outline emphasizing lighting in architectural.


Neon Flex can be controlled by DMX, SPI, PWM, RF, DALI, dimmed or programmed. We offer 3 years guarantee for indoor installations (or 2 years for outdoor installations).




Easy to cut



Aluminum channel  
(1m, 2m, 3m)



5cm Aluminum channel



IP68 (DIY Screw & Snap Connector)



Straight Exit Connector



Bottom Exit Connector



Side Exit Connector



End Cap


IP65 (DIY Connector)




Straight Exit



Side Exit ( L )



Side Exit ( R )




End Cap

■ CUSTOM PACKAGE

Small Package For Distributors (5m, 10m Roll)

Giftbox



Connection diagram (12V/24V)

