

FEATURES & BENEFITS

- DYNAMIC PIXEL RGBW COLOR
- High Brightness Output
- The Light Strip Can Be Recessed Or Surface Mounted
- Installation Indoor Or Outdoor
 Available
- High Quality, Rest Assured Service
- salt Water Resistant
- Solvent Resistant
- Uv <u>Resistant</u>
- Flame Resistant

LED LIGHT STRIP

WJ-SLS-1404-RGBW-D-12V/24V





TECHNICAL INFORMATIONLight Strip Specifications

Model:	WJ-SLS-1404-RGBW-12V/24V	
Material:	Silicone	
Bending direction:	Vertical	
Working Mode:	PWM/DMX	
LED Type:	SMD5050 (4IN1)	
Input voltage:	12V	24V
LED Qty/meter:	60pcs	60pcs
Cutting Unit:	3LEDs	6LEDs
Cutting Length:	2.5cm	5cm
Max Length Single Feed:	5m	10m
Power/m :	25W	

Driver Require





UV Resistant



-25 C

Flame Resistant

Ambient Temp

DESCRIPTION

As one of our small size, flexible LED Light Strip, The 14×4mm offers a non-s potting, fully diffused light output. The splashproof silicon coating is fully fl exible with a bend diameter of up to 10mm, making it ideal for use in signa ge and display installations both indoors and outdoors.

Neon Flex is a durable fully diffused linear light perfect for furniture and signage manufacturers thanks to it's easy to install plug and play technology. This neon can be cut easily to your desired lengths at the allocated cut points. Maximum length at any time is 5 metres before visible voltage drops occur.

This 5m kit comes with everything you will need for installation, including mounting brackets, endcaps, silicone sealant.

LED Light Strip can be dimmed via mains dimming, DALI, DMX, RF or 0-10 controllers.

Our 14×4mm Micro Neon Flex comes with a 3 year guarantee as standard on indoorinstallations (1 year on outdoor installations).









COLORFUL BOX

REEL / WHITE BOX

REEL / ANTIATATIC BAG

BAG ENGINEER BULK PACKAGE



