

602-1B

煤矿用钢丝编织液压橡胶软管


Wire Braided Hydraulic Hose For Coal Mine

结构: 软管由一层耐油合成橡胶内胶层、一层钢丝编织增强层和一耐油、耐天候的合成橡胶外胶层组成。

应用: 适用于煤矿液压支架、综合采煤机组等液压系统输送矿物油、水基液压油或水。可在-40°C ~ +100°C(-104°F ~ 212°F)使用。推荐压力适用于脉冲少的工作条件。

CONSTRUCTION:

This hose shall consist of an inner tube of oil resistant synthetic rubber, a single steel wire braid reinforcement, and an oil and weather resistant synthetic rubber cover.



APPLICATIONS:

For delivery of water, mineral oil or water-based hydraulic oil in the hydraulic system of coal mining machinery and construction machinery, and etc. working temperature range : -40°C ~ +100°C(-104°F ~ 212°F)

型号 TYPE	公制 规格 SIZE	英制 规格 SIZE	内径 I.D.		增强层直径 W.D.		外径 O.D.		最大 工作压力 W.P.		试验压力 P.P.		最小 爆破压力 B.P.		最小弯 曲半径 Min B.R.		参考 重量 W.T
			最小	最大	最小	最大	最小	最大	Mpa	Psi	Mpa	Psi	Mpa	Psi	inch	mm	
			mm	inch	Min	Max	Min	Max	Min	max	Mpa	Psi	Mpa	Psi	Mpa	Psi	
1B-06	6	1/4	6.2	6.6	10.7	11.4	13.8	14.6	32.0	4640	45.0	6530	90.0	13050	3.94	100	0.26
1B-08	8	5/16	8.0	8.4	12.9	13.7	15.7	16.5	28.0	4060	43.0	6240	86.0	12470	4.53	115	0.43
1B-10	10	3/8	9.7	10.3	14.9	15.7	18.0	18.8	25.6	3710	36.0	5220	72.0	10440	5.11	130	0.49
1B-13	13	1/2	12.9	13.4	18.8	19.8	21.4	22.2	22.4	3250	32.0	4640	64.0	9280	7.09	180	0.64
1B-16	16	5/8	16.0	16.5	21.5	22.3	24.6	25.4	16.8	2440	26.0	3770	52.0	7540	7.87	200	0.75
1B-19	19	3/4	19.0	19.5	24.8	25.6	28.0	28.8	14.4	2090	21.0	3050	42.0	6090	9.44	240	0.84
1B-22	22	7/8	22.0	22.5	27.8	28.6	31.0	31.8	12.8	1860	16.0	2320	32.0	4640	11.02	280	1.00
1B-25	25	1	25.2	25.7	31.2	32.2	34.5	35.5	11.2	1620	14.0	2030	28.0	4060	11.81	300	0.97
1B-32	32	1-1/4	31.5	32.0	38.5	39.5	41.5	42.5	9.0	1300	13.0	1890	22.5	3260	16.54	420	1.40
1B-38	38	1-1/2	38.0	38.5	45.0	46.0	48.0	49.0	7.0	1015	10.0	1450	20.0	2900	19.68	500	1.58
1B-45	45	1-3/4	45.0	45.5	52.0	53.0	55.0	56.0	5.0	725	7.5	1090	15.0	2180	21.65	550	1.82
1B-51	51	2	51.0	51.5	58.0	59.0	61.0	62.0	3.0	435	6.0	870	7.5	1087	24.80	630	1.73