



# 2+1SC

## 导静电纤维缠绕夹钢丝排吸油橡胶软管

Static Conducting Wire Inserted Hydraulic Suction & Delivery Rubber Hose

**结构:** 胶管由耐油底胶，二层纤维缠绕，一条金属螺旋线和外胶导静电层组成。

**应用:** 适用于机场、油库、码头排、吸煤油、柴油、汽油、润滑油等。

工作温度  $-40^{\circ}\text{C} \sim +100^{\circ}\text{C} (-104^{\circ}\text{F} \sim 212^{\circ}\text{F})$ 。



### CONSTRUCTION:

This hose consists of an inner tube of oil resistant synthetic rubber, a reinforcement consisting of two plies of spiral textile fiber with a suitable spiral of body steel wire. and the synthetic rubber cover with static conducting performance.

### APPLICATIONS:

Suitable for suction and delivery of gasoline、 diesel oil

Lubrication in airport,oil depot and quay,etc. working temperature range:  $-40^{\circ}\text{C} \sim +100^{\circ}\text{C} (-104^{\circ}\text{F} \sim 212^{\circ}\text{F})$

型号 TYPE	公制 规格 SIZE	英制 规格 SIZE	外径 O.D		最大 工作压力 W.P		试验压力 P.P		最小 爆破压力 B.P		最小弯 曲半径 Min B.R		参考 重量 W.T	长度 LENGTH
			公制 mm	英制 inch	bar	Psi	bar	Psi	bar	Psi	mm	inch		
2+1S-19	19	3/4	29	1.5/3.2	10	145	15	218	30	435	152	6	0.50	40
2+1S-25	25	1	35	1.3/8	10	145	15	218	30	435	200	8	0.63	40
2+1S-30	30	1-3/16	41	1.58	10	145	15	218	30	435	240	9	0.82	40
2+1S-32	32	1-1/4	43	1.11/6	10	145	15	218	30	435	256	10	0.86	40
2+1S-35	35	1-3/8	47	1.27/32	10	145	15	218	30	435	280	11	1.03	40
2+1S-38	38	1-1/2	50	1.31/32	10	145	15	218	30	435	304	12	1.10	40
2+1S-40	40	1-9/16	52	2.1/16	10	145	15	218	30	435	320	13	1.15	40
2+1S-42	42	1-21/32	54	2.1/8	10	145	15	218	30	435	335	13.1/2	1.20	40
2+1S-45	45	1-25/32	57	2.1/4	10	145	15	218	30	435	360	14	1.28	40
2+1S-50	50	1-31/32	62	2.7/16	10	145	15	218	30	435	400	16	1.40	40
2+1S-51	51	2	63	2.31/64	10	145	15	218	30	435	400	16	1.43	40
2+1S-60	60	1-3/8	72	2.27/32	10	145	15	218	30	435	480	19	1.65	40
2+1S-63.5	63.5	2-1/2	77	3.1/32	10	145	15	218	30	435	508	20	1.98	40
2+1S-70	70	2-3/4	84	3.5/16	10	145	15	218	30	435	560	22	2.25	40
2+1S-75	75	2-15/16	89	3.1/2	10	145	15	218	30	435	600	24	2.40	40
2+1S-76	76	3	90	3.17/32	10	145	15	218	30	435	608	24	2.43	40
2+1S-80	80	3-5/32	94	3.11/16	10	145	15	218	30	435	640	25	2.54	40
2+1S-90	90	3-17/32	106	4.3/16	10	145	15	218	30	435	720	28	3.28	40
2+1S-100	100	3-15/16	117	4.19/32	10	145	15	218	30	435	800	31	3.85	40
2+1S-102	102	4	119	4.11/16	10	145	15	218	30	435	816	32	3.92	40