

Model: NKR-AC003

AC output : 7/22 kw



Specifications

Appearance	Wall Box Dimension	H32*W21*T14cm
	Weigth	8kg
	Cable length	4 meter
	Installation Method	Wall-mounted
	Box Material	Aluminum Alloy
	Screen	5 inch LCD
	Input frequency	50Hz/60Hz
	Rated power	Type 2: 7/22kw Type 1: 9kw
	Precision	Level 1
	Input Voltage	Single phase:230V±10% Three phase:400V±10%
	Output Current	Type 2:7kw-single phase 32A 22kw-three phase 32A Type 1:9kw-single phase 40A
	Consumption	<2w
Functional Features	User Interface	Emergency Stop/LED indicator/RFID

	Safety Features	Overvoltage/undervoltage protection, overload protection, leakage protection, Overcurrent protection
Communication	Internet Interface	Ethernet(WIFI, 3g/4gLTE as optional)
	OCPP	OCPP 1.6J
Working environment	Working latitude	<2000m
	Working temperature	-30° C ~ +55° C
	Working humidity	5 %~ 95%
	Protection level	IP55
	Cooling	Natural cooling
	Safety standards	IEC61851-1/2017
	Special protection	Anti-UV protection

After-sale Service

1. Two years warranty for all parts. If any parts break during the period, we will provide free replacement. Non-quality factor damage is not included.
2. One to one technical engineer support for installation&operation and communication connection assistance between your app and our OCPP platform.

Additional Accessories for Options

1. Pestle.
2. Wifi connection to Internet.
3. 3g/4g/GPRS connection to Internet.
4. Customized cable length.
5. Customized Box color and customized logo

For more charger and videos, welcome to visit:
 Website: www.cnchargepoint.com